

CHAPTER 900. DEVELOPMENT STANDARDS

SECTION 901. TRANSPORTATION

901.4. Substandard Roadway Analysis and Mitigation

A. Intent and Purpose

The intent and purpose of this section is to ensure that deficiencies on substandard roads impacted by new development are corrected or mitigated.

B. Applicability

This section applies to all development where any portion of the development has connection, either directly or indirectly, to County, local, collector, arterial, or controlled access roadways, including non-State public roadways and privately owned roadways on which anyone other than the owners travel.

This section shall apply to the following applications and substantial amendments of same filed on or after June 8, 2004:

1. Development of Regional Impact.
2. MPUD Master Planned Unit Developments, Conditional Uses, and Special Exceptions.
3. Preliminary site plans.
4. Preliminary development plans.
5. Right-of-Way Use Permits.

C. Standard of Acceptability

At least eighty (80) percent of the project traffic shall access the site from the major County road continuously on, not merely crossing, standard roads. Up to twenty (20) percent of the project traffic, but not more than 100 daily trips on any given road, will be allowed to access the site via substandard roads.

D. Analysis

1. When Required:
 - a. A Substandard Roadway Analysis shall be required for those developments generating more than 100 driveway trips, as indicated in Exhibit 901.4.A. Subthreshold projects, those generating less than 100 driveway trips, shall be responsible for substandard roadway mitigation requirements pursuant to this Section, but shall have the option of having the analysis performed by the County.

A required Substandard Roadway Analysis may be waived by the County Engineer if:

- (1) The County agrees that all roads to be accessed, as required by this Code, meet the minimum standards of this section; or
- (2) The applicant agrees to improve the roads accessed to comply with the minimum standards of this section as determined by the County.

2. Procedural Requirements

a. Methodology

Prior to undertaking a Substandard Roadway Analysis, the applicant shall prepare a written methodology statement that includes the following items and submit it for review with the appropriate review fee.

- (1) Location of development (illustrated on a map).
- (2) Proposed land uses and size.
- (3) Net external estimated daily traffic generation. If trip generation data for a specific land use is not available, then the latest version of the *Institute of Traffic Engineers (ITE) Trip Generation Manual* shall be used or other trip generation estimates as mutually agreed to by the applicant and the County Engineer. Trip generation estimates shall include separate estimates for interim trip generating uses.

Mining and Land Excavation, even as an interim use, is presumed to be a separate and distinct mining land use requiring separate trip generation estimates.

(4) Internal Capture

Internal capture estimates shall be based on the ITE acceptable methodologies. In no case will an internal capture of more than twenty (20) percent be acceptable unless the County accepts a higher internal capture percentage based on verifiable documentation; e.g., field studies of comparable sites.

(5) Passerby Capture

If passerby data for a specific land use is not available, then the latest version of the *ITE Trip Generation Manual* shall be used, or other data as mutually agreed to by the applicant and the County Engineer. In no event shall the total passerby trips entering and exiting a site exceed the (10) percent of the total background traffic on the adjacent roadway.

(6) Estimated distribution and assignment of daily traffic.

(7) Indication of proposed, potentially substandard roads to be reviewed.

The County Engineer will review and comment on the acceptability of the proposed methodology.

b. Analysis Requirements

The substandard roadway assessment is not intended to be a topographic survey of the impacted roadways, but rather a "windshield survey," supplemented with appropriate field measurements and "ground observations" when potentially substandard conditions are observed.

E. Submittal Information

1. The Substandard Roadway Analysis shall contain all the necessary data and assessment, and a list of any potential improvements that are needed to achieve the above "eighty (80) percent rule" and shall be signed and sealed by a Florida registered professional engineer. The data and assessment shall be sufficient for the County Engineer's review and approval of the substandard section of the study. The assessment shall include a statement as to whether the existing typical condition meets the standards; a general description of physical constraints that may prevent upgrading the substandard condition to a standard condition and a proposal of alternative standards, if necessary; and a detailed description of the proposed improvements and associated costs.

2. Lane Width and Shoulders

a. Data Collection: The lane and shoulder widths that represent a typical lane and shoulder width of the impacted roadways shall be field measured and reported. Extreme variations from the existing typical widths shall also be reported.

b. Standards: The minimum lane and shoulder widths allowed are provided below. The design year and speed as stated in

the below referenced tables shall mean the build-out year of the project and posted speed limit, respectively.

TABLE 901.4 A

Lane and Shoulder Widths—Rural Multilane

Design Year AADT	Design Speed (mph)	Minimum Lane Width (Feet)	Minimum Shoulder Width (Feet)
ALL	ALL	12	6

TABLE 901.4 B

Lane and Shoulder Widths, Two Lane Rural and Urban—Without Curb and Gutter

Design Year AADT	Design Speed (mph)	Minimum Lane Width (Feet)	Minimum Shoulder Width (Feet)
1-750	ALL	10 ¹	6 ³
751-2000	<50	11 ¹⁻²	6 ³
	≥50	12 ²	6 ³
>2000	ALL	12 ²	6 ³

¹For rural and urban projects without curb or gutter (regardless of traffic volume), when widening is required, a minimum lane width of eleven (11) feet is required. A minimum lane width of twelve (12) feet is required if heavy vehicles are ten (10) percent or more of the total daily driveway trips.

²May be reduced by one (1) foot if heavy vehicles are less than ten (10) percent of design year traffic and are less than ten (10) percent of the total daily driveway trips.

³The required width is eight (8) feet if heavy vehicles are ten (10) percent or more of the total daily driveway trips.

TABLE 901.4 C

Urban Multilane or Two Lane with Curb and Gutter

Design Year AADT	Design Speed (mph)	Minimum Thru-Lane (Feet)	Minimum Turn Lane (Feet)	Minimum Parking Lane (Feet)
ALL	ALL	10 ¹	9 ²	7 ³
<p>¹ For rural and urban projects without curb or gutter (regardless of traffic volume), when widening is required, a minimum lane width of eleven (11) feet is required. A minimum lane width of twelve (12) feet is required if heavy vehicles are ten (10) percent or more of the total daily driveway trips.</p> <p>² May be reduced by one (1) foot if heavy vehicles are less than ten (10) percent of design year traffic and less than ten (10) percent of the total daily driveway trips.</p> <p>³ A minimum width of seven (7) feet, measured from the face of the curb, may be left in place. Otherwise provide eight (8) feet minimum, measured from the face of the curb.</p>				

3. Pavement Condition

a. **Data Collection:** The thickness of the surface pavement and base and the cross slopes that represent a typical surface and base thickness, and cross slopes of the impacted roadways shall be field measured and reported. The thickness of the subbase need not be field measured unless practical. If the subbase is not measured, the thickness of the subbase can be assumed standard. In addition, any quarter-panel failures and wheel-rutting shall be noted and reported. Extreme variations from the existing typical conditions shall also be reported.

b. **Standards:** The minimum structural numbers for roadways are:

- (1) Local Streets in AG (Agricultural) and AG/R (Agricultural/Rural) Land Use Less Than Sixteen (16) Lots and RES-1 (Residential - 1 du/ga) Land Use Less Than Ten (10) Lots: 1.89
- (2) Local Streets: 2.19
- (3) Subdivision Collector (Type I): 3.24
- (4) Major Collector: 3.42

A minimum structural number of 4.00 is required on local and collector roadways if heavy vehicles are ten (10) percent or more of the total daily driveway trips.

Layer coefficients are provided in Tables 901.4 D and 901.4 E below:

TABLE 901.4 D

Structural Coefficients for Different Pavement Layers

Specification Section	Layer Coefficient	Layer
337	0.00	FC-2
337	0.22	FC-3
331	0.44	Type S
333	0.30	Type III
332	0.20	Type II
280	0.30	ABC-3 (Marshall - 1,000)
280	0.25	4ABC-2 (Marshall - 750)
280	0.20	ABC-1 (Marshall - 500)
272	0.25	Econocrete (1,100 psa)
272	0.22	Econocrete (800 psi)
270	0.20	Soil Cement (500 psi)
270	0.15	Soil Cement (300 psi)
335	0.15	SAHM (Marshall - 300)
204	0.15	Graded Aggregate (LBR-100)
250	0.18	Cemented Coquina Shell (LBR-100)
200	0.18	Limerock (LBR-100)
250	0.16	Bank Run Shell (LBR-100)
230	0.12	Limerock Stabilized (LBR-70)
240	0.12	Sand Clay (LBR-75)
260	0.10	Shell Stabilized (LBR-70)
160-3	0.10	Stabilized Subbase
180	0.08	Stabilized Subbase
160-2	0.08	Type B Stabilized (LBR-40)
160-2	0.06	Type B Stabilized (LBR 30)
160-2	0.06	Type C Stabilized
170	0.12	Cement Treated Subgrade (300 psi)
165	0.08	Lime Treated Subgrade
N/A	0.15	Crushed Concrete (Reclaimed Concrete Aggregate Base, LBR 150)

TABLE 901.4 E
Reduced Structural Coefficients
Asphaltic Materials

Layer	Original Design	Pavement Condition		
		Good	Fair	Poor
Type I	0.37	0.30	0.23	0.15
Binder	0.30	0.25	0.20	0.15
SBRM (300 M)	0.15	0.13	0.11	0.08
FC-3	0.22	0.17	0.15	0.12
Type S	0.44	0.34	0.25	0.15
Type III	0.30	0.25	0.20	0.15
Type II	0.20	0.17	0.15	0.12
ABC-3 (1,000 M)	0.30	0.25	0.20	0.15
ABC-2 (750 M)	0.25	0.20	0.16	0.12
ABC-1 (500 M)	0.20	0.17	0.14	0.10
SAHM (300 M)	0.15	0.13	0.11	0.08

NOTE: Reduced structural coefficients for use in the AASHTO Flexible Pavement Design Equation can be obtained from this table for all asphalt layers based on pavement condition. Pavement condition for this table should be based on the surface appearance of the asphalt pavement (cracking, patching, rutting, etc.) and may be supplemented by additional testing. Structural coefficients are not reduced for existing rock base, subbase, or subgrade.

Recommended Criteria:

Good: No cracking, minor rutting/distortion.

Fair: Crack Rating = eight (8) or higher, minor rutting/distortion.

Poor: Crack Rating = less than eight (8), rutting = $\frac{3}{8}$ inch or greater.

NOTE: Quarter-panel failures and wheel rutting are considered to be substandard conditions.

Roadway cross slopes shall conform to Table 901.4 F below:

TABLE 901.4 F
Roadway Cross Slopes

Feature	Standard	Range
Travel Lanes	0.02	0.02-0.04 ¹
Shoulders	0.06	0.03-0.08 ²
Parking Lanes	0.05	0.03-0.05

¹ Existing multilane curb and gutter sections originally constructed with a parabolic crown section may be resurfaced using a series of tangents with a cross slope range from 0.015-0.05.

² When existing shoulders are to remain, the algebraic difference between the shoulder slope and adjoining roadway pavement slope shall be ≤ 0.07 .

4. Flooding

- a. Data Collection: Data collection shall include the compilation of historical flooding locations readily available from the Development Services Branch. The flooding location Geographic Information System map layer titled "Observed Flooding" shall be used to identify flooding areas.
- b. Standards: The standard is no surface ponding upon roadway.
- c. Assessment: The assessment shall include a statement as to whether impacted roadways are within the flood area, a general description of physical constraints that may prevent upgrading the substandard condition to a standard condition, and proposed alternative standards, and a detailed description of the proposed improvements and associated costs.

5. Side Slope

- a. Data Collection: The front and back slopes that represent a typical front and back slope of the impacted roads shall be field measured and reported. Extreme variations from the existing typical conditions shall also be reported.
- b. Standards: The maximum front slope shall be one to four (1:4) within the clear zone and one to three (1:3) outside the clear zone. However, front slopes of one to three (1:3) or flatter may remain within the clear zone, but shielding may be required. Front slopes steeper than one to three (1:3) shall be shielded per *FDOT Design Standards*, Index 400, General Notes, as may be amended. Consideration should be given to

flattening slopes of one to three (1:3) or steeper at locations where run off the road type crashes are likely to occur; e.g., on the outside of horizontal curves.

The maximum back slope shall be one to three (1:3) in the clear zone. The maximum back slope shall be one to two (1:2) outside the clear zone without shielding.

- c. **Assessment:** The assessment shall include a statement as to whether the existing conditions meet the standards, a general description of physical constraints that may prevent upgrading the substandard condition to standard and proposed alternative standards, and a detailed description of the proposed improvements and associated costs.

6. **Clear-Zone Widths**

- a. **Data Collection:** The clear-zone widths that represent a typical clear-zone width of the impacted roads shall be field-measured and reported. Extreme variations from the existing typical conditions shall also be reported.
- b. **Standards:** Minimum clear-zone widths shall be as listed below on Table 901.4 G. The design speed shall mean the posted speed limit.

TABLE 901.4 G

Clear-Zone Width (Feet)

Design Speed (mph)	Travel Lanes and Multilane Ramps	Auxiliary Lanes and Single-Lane Ramps
<45	6	6
45*	14	8
>45	18	8

General Notes for Table 901.4 G

When relocation is required to meet minimum clear-zone requirements, consideration should be given to providing new construction widths.

Clear-zone widths are for side slopes one to four (1:4) and flatter. For steeper slopes, provide a clear, run-out area at the toe of the fill.

When crash history indicates the need, or where specific site investigation shows definitive crash potential, clear-zone widths shall be adjusted on the outside of horizontal curves with flush shoulders.

Clear-zone width is measured from the edge of the traveled way.

*May be reduced to < 45-mph widths if conditions more nearly approach those for low speed (40 mph or less).

TABLE 901.4 H

Horizontal Clearance for Traffic Control Signs

Placement	Placement shall be in accordance with the <i>FDOT Design Standards</i> . Placement within sidewalks shall be such that an unobstructed sidewalk width of four (4) feet or more (not including the width of the curb) is provided.
Supports	Supports, except overhead sign supports, shall be frangible or breakaway. When practicable, sign supports should be located behind barriers that are justified for other reasons. Overhead sign supports shall be located outside the clear zone unless shielded.

TABLE 901.4 I

Horizontal Clearance for Light Poles

Conventional Lighting	<p>Not in the median, except in conjunction with barriers that are justified for other reasons.</p> <p>Rural (Flush Shoulders): Twenty (20) feet from the travel lane and fourteen (14) feet from the auxiliary lane (may be clear-zone width when the clear zone is less than twenty (20) feet).</p> <p>Urban (Curb and Gutter): From the right-of-way line to four (4) feet back from the face of the curb (may be 1.5 feet back from the face of the curb when all other alternatives are deemed impractical). Placement within sidewalks shall be such that an unobstructed sidewalk width of four (4) feet or more (not including the width of the curb) is provided.</p>
High Mast Lighting	Outside the clear-zone unless shielded.

TABLE 901.4 J

Horizontal Clearance for Utility Installations

Shall not be located within the limited access right-of-way, except as permitted by the Telecommunications Facilities on Limited Access Rights-of-Way Policy (Topic No. 000-625-025).

Shall not be located in the median.

Flush Shoulders:

Not within the clear zone. Install as close as practical to the right-of-way without aerial encroachments onto private property.

Curb or Curb and Gutter:

At the right-of-way line or as close to the right-of-way line as practical. Must maintain 1.5 feet clear from the face of the curb. Placement within sidewalks shall be such that an unobstructed sidewalk width of four (4) feet or more (not including the width of the curb) is provided.

See the *Utility Accommodation Manual*, Topic No. 710-020-001, for additional information.

TABLE 901.4 K

**Horizontal Clearance to Signal Poles
and Controller Cabinets for Signals**

Shall not be located in medians.

Flush Shoulders:

Outside the clear zone.

Curb or Curb and Gutter:

Four (4) feet from the face of outside curbs and outside the sidewalk. However, when necessary, the signal poles may be located within sidewalks such that an unobstructed sidewalk width of four (4) feet or more (not including the width of the curb) is provided. Also, when site conditions make the four (4) foot clearance impractical, clearance may be reduced to 1.5 feet.

TABLE 901.4 L

Horizontal Clearance to Trees

Minimum horizontal clearance for new plantings shall meet new construction criteria.

Minimum horizontal clearance to existing trees where the diameter is or is expected to be greater than four (4) inches when measured six (6) inches above the ground shall be:

Flush Shoulders:

Outside the clear zone.

Curb or Curb and Gutter:

1.5 feet from the face of outside curbs.

3.5 feet from the edge of the inside traffic lane where a median curb is present.

TABLE 901.4 M

Horizontal Clearance to Bridge Piers and Abutments

Minimum horizontal clearance to bridge piers and abutments:

Flush Shoulders:

Outside the clear zone.

Curb or Curb and Gutter:

Sixteen (16) feet from the edge of the travel lane.

TABLE 901.4 N

**Horizontal Clearance to Railroad Grade
Crossing Traffic Control Devices**

Placement shall be in accordance with the design standards.

TABLE 901.4 O

Horizontal Clearance to Other Roadside Obstacles

Minimum horizontal clearance to other roadside obstacles:

Flush Shoulders:

Outside the clear zone.

Curb or Curb and Gutter:

Four (4) feet back from the face of the curb. May be 1.5 feet back from the face of the curb when all other alternatives are deemed impractical.

- c. Assessment: The assessment shall include a statement as to whether the existing conditions meet the standards, a general description of physical constraints that may prevent upgrading the substandard condition to standard and propose alternative standards, and a detailed description of the proposed improvements and associated costs.

7. Railroad Crossing Traffic Control

- a. Data Collection: Document/inventory existing control devices and other data needed to assess conditions relative to the following issues:
 - (1) Traffic control (presence and advance visibility of signing and markings; need for beacons and gates);
 - (2) Minimum crossing sight distance requirements;
 - (3) Road surface smoothness (vertical alignment); and
 - (4) Road surface width through crossing.
- b. Standards: As required by the following:
 - (1) Traffic Control: *Manual on Uniform Traffic Control Devices* (MUTCD), Chapter 8; Federal Highway Administration (FHWA) Report FHWA-TS-86-215 or current edition; and Florida Department of Transportation (FDOT) *Design Standards*, Indices 17881 and 17882, as may be amended.
 - (2) Sight Distance at Passive Crossing: *AASHTO Green Book*, Case 1, latest edition; and *FDOT Manual of Uniform Minimum Standards for Design, Construction, and Maintenance for Streets and Highways*, latest edition.
 - (3) Road Surface Smoothness and Width Through Crossing: *FDOT Plans Preparation Manual*, Volume 1, Chapter 6, as amended; and *FDOT Design Standards*, Indices 560, 17881, and 17882, as may be amended.
- c. Assessment: Compare existing conditions with the requirements of the MUTCD and FDOT standards, and undertake analysis to determine the need for improvements. If improvements are needed, consult with the FDOT and CSX Railroad Company for agreement or disagreement and recommend appropriate improvements.

8. Cost Estimate: The applicant shall prepare an estimate of the cost to cure the substandard conditions, and the County's Development Services Branch shall be the agency to review and accept the cost estimate. The Development Services Branch may develop and maintain average unit costs for estimating the costs of upgrading substandard roads.

F. Mitigation

1. For Projects Conducting Analysis

- a. The required mitigation for substandard roads shall be the payment of the development's fair share of the cost of designing, constructing, and acquiring right-of-way for all the improvements needed to achieve the eighty (80) percent rule and the applicable minimum roadway design and maintenance standards. The fair share shall be calculated in accordance with the following equation:

$$\text{Developer Share} = \text{Daily Development Trips} / (\text{Existing AADT} + \text{Daily Development Trips}).$$

- b. The required mitigation for proposed development that exceeds the maximum entitlements of the existing zoning or land use (whichever is more restrictive) shall be the design, construction, and right-of-way donation/acquisition for all the improvements needed to achieve the eighty (80) percent rule and the applicable minimum roadway design and maintenance standards.

2. For Projects Exempt from Analysis

- a. Fair-share payment required: Developments generating less than or equal to 100 driveway trips (Substandard Road Subthreshold Developments) shall be required to pay a substandard road fair-share payment, calculated by the County if the development has access or is required to have access to a substandard road or roads (as defined above).
- b. Assessment by the County: For Substandard Road Subthreshold Developments, the assessment of whether the road(s) to be accessed are substandard, and the estimate for correcting substandard conditions shall be prepared by the County Engineer. For Substandard Road Subthreshold Developments, the calculation of the fair-share payment shall be based upon the cost estimate for correcting substandard conditions prepared by the County Engineer and shall be computed using: (1) County Paving Assessment equivalent residential unit assessment methodology for local roads; (2) the fair-share formula set forth above for subdivision

collector roads, or (3) other appropriate methodology established by the County.

- c. Option to prepare analysis: Any Substandard Road Subthreshold Development that disagrees with the Substandard Roadway Analysis (SRA), the cost estimate for correcting substandard conditions, or the calculation of the fair-share payment as determined by the County shall have the right to prepare an SRA in accordance with the requirements set forth in this section. For the purposes of this subsection, the term "development" shall be defined as a "project" pursuant to the definition in this Code's Definitions.

Any substandard road fair-share payment collected by the County shall be budgeted separately and shall be utilized only to correct substandard conditions on one (1) or more of the roads which formed the basis of the fair-share calculation or on other substandard roads which will benefit the fee payer.

G. Relief

The County Engineer is authorized to grant deviations from the requirements of Section 901.4.D or 901.4.E pursuant to Section 303.6.C or 407.5, as applicable. Relief from the remaining provisions of this section may only be granted by the Board of County Commissioners in accordance with Section 407.4 or 407.5.

EXHIBIT 901-4

EXHIBIT A PASCO COUNTY TIS GUIDELINES SIZE OF DEVELOPMENT THAT GENERATES OVER 100 DAILY TRIPS

LAND USE	TRIP RATE (1)	SIZE OF DEV.	UNIT
RESIDENTIAL:			
Single-Family (Detached)	7.59	14	Du
Multiple Family (Apartments)	6.30	16	Du
Mobile Home Park	4.67	22	Du
Age-Restricted Single-Family	3.71	27	Du
Congregate-Care Facility (Attached)	2.25	45	Du
Low-Rise Condominium (1 to 2 Stories)/Townhouse	5.20	20	Du
High-Rise Condominium (3 or More Stories)	4.18	24	Du

LODGING:			
Hotel	8.30	13	Room
Motel	5.63	18	Room
Resort Hotel	5.10	20	Room
Recreational Vehicle Park	3.70	28	RV Space

RECREATION:			
Marina	2.96	34	Berth
Golf Course	35.74	3	Hole
Miniature Golf Course	3.30	31	Hole
Movie Theaters	106.63	1	Screen
General Recreation	2.28	44	Acres
Racquet Club/Health Club/Spa/Dance Studio	14.03	8	1,000 SF
Bowling Alley	33.33	4	1,000 SF
Community Center	22.88	5	1,000 SF

INSTITUTIONAL:			
Hospital	17.57	6	1,000 SF
Nursing Home	2.48	41	Bed
Elementary School	1.29	78	Student
Middle School	1.62	62	Student
High School	1.71	59	Student
Junior/Community College	1.20	84	Student
University	2.38	43	Student
Church	9.11	11	1,000 SF
Day Care	3.03	34	Student
Cemetery	4.73	22	Acres

OFFICE:			
General Office - 50,000 SF or Less	15.65	7	1,000 SF
General Office - 50,001 to 100,000 SF	14.25	All	1,000 SF
General Office - 100,001-200,000 SF	12.15	All	1,000 SF
General Office - 200,001-400,000 SF	10.36	All	1,000 SF

OFFICE (cont.)			
General Office - Greater than 400,000 SF	8.83	All	1,000 SF
Medical Office	35.95	3	1,000 SF
Office Park	11.70	9	1,000 SF
Veterinarian Clinic	32.80	4	1,000 SF

RETAIL:			
Specialty Retail	49.99	3	1,000 SF
Shopping Center - Under 50,000 GSF	86.56	2	1,000 SF
Shopping Center - 50,000 to 200,000 GSF	62.81	All	1,000 SF
Shopping Center - 200,001 to 400,000 GSF	46.23	All	1,000 SF
Shopping Center - 400,001 to 600,000 GSF	38.66	All	1,000 SF
Shopping Center - 600,001 to 800,000 GSF	34.37	All	1,000 SF
Shopping Center - Greater than 800,000 GSF	30.33	All	1,000 SF
Pharmacy/Drug Store with Drive-Through	95.21	2	1,000 SF
Home Improvement Superstore	29.80	4	1,000 SF
Hardware/Paint	51.29	2	1,000 SF
Quality Restaurant	91.10	2	1,000 SF
High-Turnover Restaurant	126.50	1	1,000 SF
Fast-Food Restaurant with Drive-Through	522.62	All	1,000 SF
Gasoline Station	168.56	1	Fuel Pos
Quick Lube	40.00	3	Bays
Auto Repair or Body Shop	30.09	4	1,000 SF
Self-Service Car Wash	108.00	1	Bay
Tire Store	24.87	5	1,000 SF
New/Used Auto Sales	32.93	4	1,000 SF
Supermarket	103.38	1	1,000 SF
Convenience Store with Gas Pumps	803.24	All	1,000 SF
Furniture Store	5.06	20	1,000 SF
Bank/Savings Drive-In	281.55	All	1,000 SF
Convenience/Gasoline/Fast-Food Store	984.59	All	1,000 SF

INDUSTRY:			
General Light Industrial	6.97	15	1,000 SF
General Heavy Industrial	1.50	67	1,000 SF
Industrial Park	6.96	15	1,000 SF
Manufacturing	3.82	27	1,000 SF
Warehouse	4.96	21	1,000 SF
Miniwarehouse	2.50	41	1,000 SF
High-Cube Warehouse	1.20	84	1,000 SF
Airport Hangar	4.96	21	1,000 SF

NOTES: For land uses not listed herein, or land uses with higher weekend trip generation, either the *ITE Trip Generation Handbook*, latest edition, or other trip-generation studies as approved by the County shall be used.

To estimate total daily driveway trips for land uses listed herein with heavy vehicles that are 10 percent or more of the total daily driveway trips, the total estimated daily driveway trips for heavy vehicles shall be multiplied by 2, unless ITE heavy vehicle data or other County-approved heavy vehicle trip generation data for the land use support a different multiplier; however, in no event shall the multiplier be less than 1. The size of development thresholds listed herein may be reduced based on additional heavy vehicle trips.

Source: Pasco County 2006 Transportation Impact Fee Update Study Summary Report.